



**Safety Tech Outrigger Pads** deliver the safety, quality and performance you expect from the industry leader.

## Stock Models

MODEL	LOAD CAPACITY		WIDTH	LENGTH	HEIGHT	WEIGHT	SQ.IN.
	VERTICAL	45 DEGREE					
<b>PAD1515.75</b>	40,000# (KG20,412)	18,000# (KG9,072)	15" (C38.1)	15" (C38.1)	.75" (C1.905)	5.5# (KG3.40)	225 (CT1,451.70)
<b>PAD18181</b>	55,000# (KG24,948)	30,000# (KG13,608)	18" (C45.72)	18" (C45.72)	1" (C2.54)	11.0# (KG4.99)	324 (CT2,090.45)
<b>PAD24241</b>	60,000# (KG27,216)	35,000# (KG15,876)	24" (C60.96)	24" (C60.96)	1" (C2.54)	20.0# (KG9.07)	576 (CT3,761.35)
<b>PAD24242</b>	62,000# (KG28,123)	40,000# (KG18,144)	24" (C60.96)	24" (C60.96)	2" (C5.08)	38.0# (KG17.24)	576 (CT3,761.35)
<b>PAD30301</b>	81,000# (KG36,741)	41,000# (KG18,597.6)	30" (C76.2)	30" (C76.2)	1" (C2.54)	31.0# (KG14.06)	900 (CT5,806.8)
<b>PAD36361</b>	93,000# (KG42,184.8)	43,000# (KG19,504.8)	36" (C91.44)	36" (C91.44)	1" (C2.54)	45.0# (KG20.41)	1296 (CT8,361.79)
<b>PAD48481</b>	135,000# (KG61,236)	52,000# (KG23,587.2)	48" (C121.92)	48" (C121.92)	1" (C2.54)	80.0# (KG36.29)	2304 (CT14,865.4)
<b>PAD30302</b>	85,000# (KG38,556)	43,000# (KG19,504.8)	30" (C76.2)	30" (C76.2)	2" (C5.08)	62.0# (KG28.12)	900 (CT5,806.8)
<b>PAD36362</b>	98,000# (KG44,252.8)	45,000# (KG20,412)	36" (C91.44)	36" (C91.44)	2" (C5.08)	90.0# (KG40.83)	1296 (CT8,361.79)
<b>PAD48482</b>	140,000# (KG63,504)	55,000# (KG24,948)	48" (C121.92)	48" (C121.92)	2" (C5.08)	160.0# (KG72.58)	2304 (CT14,865.4)

## Safety Tech Pad Features

- RELIABLE LOAD DISTRIBUTION
- LIGHTWEIGHT
- SAFETY TEXTURING
- MEMORY RECOVERY
- LIFETIME GUARANTEE

**MAKE YOUR SETUP SAFE.**

\*8" X 10" OUTRIGGER LEG APPLIED UNDER TWO SEPARATE CONDITIONS: 10,000# VERTICALLY & 10,000# WITH A 45° ANGLE.  
 \*\*HANDLE LOCATED ON WIDTH SIDE OF ALL PADS. PADS 900 SQ. IN. & LARGER HAVE 2 OR MORE HANDLES OPPOSITE EACH OTHER.  
 \*\*\*CUSTOM SIZE PADS ARE AVAILABLE. REQUIRES A MINIMUM ORDER. LEAD TIME FOR NON-STOCK ITEMS IN 30-45 DAYS  
 KEY: C = CENTIMETERS; KG = KILOGRAMS; CT = SQUARE CENTIMETERS

- NOTICE**
- FOOT PADS MUST BE SMOOTH AND HAVE 80 SQ. IN. OF SURFACE
  - MUDDY OR LOOSE SOIL CONDITIONS MAY REQUIRE ADDITIONAL SHORING OR STACKING OF PADS
  - EXCESSIVE FLEXING AND/OR BENDING MAY SHORTEN THE USABLE LIFE OF THE PAD.
  - ACCEPTABLE OPERATING TEMPERATURE IS -40° TO 180° F

[Sales@AtlanticSupply.com](mailto:Sales@AtlanticSupply.com)



## ATLANTIC SUPPLY

Largo, FL 800-752-9416  
 Riviera Beach, FL 800-535-7384  
 Orlando, FL 800-569-8950  
 Jacksonville, FL 888-260-5584  
 Montgomery, AL 866-917-3447

[www.AtlanticSupply.com](http://www.AtlanticSupply.com)  
[www.ScalesForBusiness.com](http://www.ScalesForBusiness.com)